

**El Dorado County**  
**Air Quality Management District**  
Automotive Refinishing Coating Supplemental Questionnaire

Business Name: \_\_\_\_\_ Spray Booth No. \_\_\_\_\_ Date: \_\_\_\_\_  
Prepared By: \_\_\_\_\_  
Brand(s) of Coatings Normally Used: \_\_\_\_\_

Coating Type	VOC Content in lb/gal *	Maximum Coating Usage (gallons)					
		Daily	1st Qtr <sup>1</sup>	2 <sup>nd</sup> Qtr <sup>1</sup>	3 <sup>rd</sup> Qtr <sup>1</sup>	4 <sup>th</sup> Qtr <sup>1</sup>	Annual <sup>2</sup>
Pretreatment Wash Primer							
Precoat							
Primer/Primer Surfacer							
Primer Sealer							
Solid Color Topcoat							
Metallic Topcoat <sup>3</sup>							
Multi-Stage topcoat System <sup>4</sup>							
Specialty Coating							
Temporary Protective Coating							
Surface Prep. Solvent (For Metals)							
Surface Prep. Solvent (For Plastics)							

\*Typical volatile organic compound (VOC) content RTS (ready to spray), in pounds per gallon.

**Notes**

1. Quarterly usage estimates should consider the maximum possible business in each quarter.
2. The maximum annual usage will be equal to or less than the sum of the four quarterly maximum usages.
3. Metallic topcoat usage for single stage (i.e., enamel) applications only. Multi-stage applications (i.e., metallic basecoat with a clear coat) should be included under multi-stage topcoat system usage.
4. Multi-stage topcoat system usage should include groundcoats, midcoats, and clearcoats.