

PLANNING AND BUILDING DEPARTMENT

BUILDING DIVISION

Building Division - El Dorado County (ca.gov)

PLACERVILLE OFFICE:

2850 Fairlane Court, Placerville, CA 95667

BUILDING
(530) 621-5315
bldgdept@edcgov.us
PLANNING
(530) 621-5355
planning@edcgov.us

LAKE TAHOE OFFICE: 924 B Emerald Bay Rd South Lake Tahoe, CA 96150

(530) 573-3330 tahoebuild@edcgov.us

Defensible Space Guidelines

Defens	sible Space Zone (within 30 feet of all structures or to property line):		
	Remove all branches within 10 feet of any stovepipe or chimney outlet. PRC §4291(a)(4)		
	Remove leaves, needles or other vegetation on roofs, gutters, decks, porches and		
	stairways etc. PRC§4291(a)(6)		
	overhanging buildings. PRC§4291(a)(5)		
	Prune lower branches of trees up to a height of 6 to 15 feet (1/3 tree height for trees under 18 feet). PRC§4291(a)(1)		
	Remove all dead or dying grass, leaves, needles or other vegetation. PRC§4291(a)(1)		
	luced Fuel Zone (within 30 – 100 feet of all structures or to property line):		
	☐ Mow dead or dying grass to a maximum of 4 inches in height. Trimmings may		
Ш	remain on the ground. PRC§4291(a)(1)		
	Live flammable ground cover less than 18 inches in height may remain, but overhanging and		
Ш	adjacent trees must be pruned to a height of 6 to 15 feet. PRC§4291(a)(1)		
	Reduce fuels in accordance with the Continuous Tree Canopy Standard (see back).		
	PRC§4291(a)(1)		
	Reduce fuels in accordance with the Horizontal Spacing Standard (see back). PRC§4291(a)(1)		
	sible and Reduced Fuel Zone (within 100 feet of all structures or to property line):		
□ Logs or stumps embedded in the soil must be removed or isolated from structures			
	and other vegetation. PRC§4291(a)(1)		
	Remove all dead or dying brush and trees, and all dead or dying tree branches within 15		
	feet of the ground. PRC§4291(a)(1)		
	lect of the ground. I $(c\sqrt{42})^2(a)(1)$		
Other	Requirements:		
	•		
	and above propane tanks. CFC §3807.3		
	Address numbers shall be displayed in contrasting colors (4"Min Size) and readable from the street or access road. CFC §505.1		
	Equip chimney or stovepipe openings with a metal screen having openings between 3/8 inch		
_	and 1/2 inch. CBC §2113.9.1		
	v		
_			
	mendations:		
	Clear 10 feet around and 15 feet above fuels (e.g. woodpiles, lumber, scrap etc.). Move		
	woodpiles as far as possible from structures.		
	Remove flammable materials stored under decks and similar overhangs of structures.		
	Clear vegetation 10 feet from sides and 15 feet above all driveways and turnaround areas.		

Continuous Tree Canopy Standard

To achieve defensible space while keeping a larger stand of trees with a continuous tree canopy, adhere to the guidelines below:

- Prune lower branches of trees to a height of 6 to 15 feet from the top of the vegetation below or 1/3 to 1/2 the tree height for under 30 feet, whichever is less.
- Remove all ground fuels greater than four inches in height. Single trees or other vegetation may be kept if they are well spaced, well pruned, well maintained, free of all dead material, and will not spread fire to other vegetation or structures.

Horizontal Spacing Standard

- Beyond 30 feet from structures grass should not exceed four inches in height. In situations where these fuels are isolated from other fuels or where necessary to stabilize soil, grasses may reach a height of 18 inches.
- Clearance between shrubs should be 4 to 40 feet depending on the slope of the land and size and type of vegetation. Check the chart below for an estimation of clearance distance.

Minimum Horizontal Spacing Guidelines			
Slope	Shrubs, Ground Covers & Other Ornamental Plants	Trees	
_	Space required between clumps of ground cover,	Space required between tree	
	plants, bushes, shrubs, seedlings, or sapling trees,	canopies or groups of trees	
	etc		
Flat or gentle slope (0% to 20%)	2 times the height of the plant	10 feet	
Moderate slope (20% to 40%)	4 times the height of the plant	20 feet	
Steep slope (greater than 40%)	6 times the height of the plant	30 feet	