

City/State/Zip:

PLANNING AND BUILDING DEPARTMENT

https://www.eldoradocounty.ca.gov/Land-Use/Building-Services

PLACERVILLE OFFICE:

2850 Fairlane Court, Placerville, CA 95667

BUILDING
(530) 621-5315
bldgdept@edcgov.us
PLANNING
(530) 621-5355

planning@edcgov.us

LAKE TAHOE OFFICE:
924 B Emerald Bay Rd
South Lake Tahoe, CA 96150
(530) 573-3330
bldgdept@edcgov.us

CEPE#

Phone:

NON-RESIDENTIAL COOL ROOF FORM PE	RMIT APPLICAT	TION (PART 9-C)	Permit #	
FOR NON-RESIDENTIAL RE-ROOFS				
1. RE-ROOFS MUST MEET ENERGY CODE REQUIREMENTS FOR COOL ROOFS –See the Non-Residential Manual and				
§110.8(i) of the 2016 California Energy Code.				
2. SOME EXEMPTIONS MAY APPLY. CHECK BOX IF APPLICABLE AND PROVIDE DOCUMENTATION				
The area of roofing replacement is less than 2,000 sq.ft., or less than 50% of the roof area, whichever is less				
The entire building has been analyzed under the Performance Approach				
The roof area is covered by building integrated photovoltaic panels				
Roof has a thermal mass over the roof membrane with a weight of at least 25 lb/ft ²				
3. IN ORDER TO MEET ENERGY CODE, ROOFING PRODUCTS MUST BE LISTED BY COOL ROOF RATING COUNCIL				
(CRRC) and must meet minimum values as shown:				
Low Slope roofs ($\leq 2:12$) Steep Slope roofs ($> 2:12$)				
Aged Solar reflectance0.63 OR SRI75 Aged Solar Reflectance				
Thermal Emittance0.75 Thermal Emittance0.75				
4. PROVIDE INFORMATION AS REQUESTED ON THE FOLLOWING:				
Roof Slope Prod	uct Type ²	Aged Solar	Thermal	
CRRC Product ID Number $ \le 2:12 > 2:12 $	51	Reflectance 3, 4	Emittance SRI ⁵	
		1 ⁴		
		4		
ПП		14		
1. The CRRC Product ID Number can be obtained t	from the Cool Roof Ra	ting Council's Rated F	Product Directory at:	
1. The CRRC Product ID Number can be obtained from the Cool Roof Rating Council's Rated Product Directory at: https://coolroofs.org/directory/wall				
2. Indicate the type of product being used for the roof top (i.e. single-ply roof, asphalt roof, metal roof, etc.)				
3. If the Aged Reflectance is not available in the Cool Roof Rating Council's Rated Product Directory, then use the Initial				
Reflectance value from the same directory and use the equation (0.2 + 0.7 (ρ initial – 0.2) to obtain a calculated aged				
value, where ρ is the Initial Solar Reflectance.				
4. Check box if the Aged Reflectance is a calculated value using the equation above.				
5. SRI value may be calculated by using the SRI-Worksheet at http://www.energy.ca.gov/title24/. Attach a copy.				
To apply Liquid Field Applied Coatings , the coating must be applied across the entire roof surface and meet the dry mil thickness or coverage				
recommended by the coatings manufacturer and meet minimum performance requirements listed in §118(i)4.				
Select the applicable coating:				
Aluminum-Pigmented Asphalt Roof Coating				
Documentation Author's Declaration Statement • I certify that this Certificate of Compliance documentation is accurate and complete.				
Name: Signature:				
Company:		Date:	Date:	
• •				
Address:		If Applicable: CEA #		